

Our KORY 3000A All-Steer Running Gear features front and rear steering assemblies designed to reduce turning radius and minimize inward tracking, making it ideal for navigating tight turns, narrow rows, and confined spaces.

SPECIFICATIONS:

LOAD CAPACITY	3000 LBS
TREAD WIDTH	41 INCHES (Center to center of tire)
OVERALL WIDTH	49 INCHES
REACH EXTENSION	52-72 INCHES
TONGUE	CLEVIS TYPE, 1-7/8 inch ball hitch can be bolted on (optional)
TIE RODS	½ INCH DIAMETER RODS W/ CLEVIS (adjustable)
WHEELS	5 BOLT
TIRES	18.5 X 8.5 – 8 2 PLY TUBELESS FLOTATION TIRES
SPINDLES	1-1/2 INCH DIAMETER
HUBS	5 BOLT HEAVY DUTY
BEARINGS	TIMKEN TAPERED ROLLER BEARINGS
BOLSTER STAKES	STANDARD
WEIGHT WITH TIRES	250 LBS
SHIP WEIGHT ON PALLET	280 LBS

KORY FARM EQUIPMENT
210 W Lantz St. Congerville, IL 61729
Ph. (815) 445-3711
Email: parts@koryfarm.com
www.koryfarm.com

Kory reserves the right to change product designs, specifications, and pricing without prior notice.